

DALI MCU rotary dimmer for DALI illuminant

Product Data Sheet



Assembly arrangement	Basic element
Method of operation	Turn/push button
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with screw
Surface protection	Untreated
Suitable for degree of protection (IP)	IP20
Dimming phase cut-on	No
Dimming phase cut-off	No
Serial dimmer	No
Substation input	No
Halogen free	Yes
Nominal voltage	230-230Volt
Frequency	50-60Hertz
Width of device	71.5Millimetre
Height of device	71.5Millimetre
Depth of device	31Millimetre

**DALI MCU rotary dimmer for
DALI illuminant**

DALI MCU rotary dimmer for DALI illuminant with 1-way/2-way push on/push off switch
Basic brightness adjustable (min./max.) with reset function, with screw terminals, for up to 25 DALI ballasts, overvoltage fuse (not
resettable), 230 V~, 50/60 Hz, DALI bus 50 mA, DALI output 16 V DC

Material No.	Article No.	EAN-code
00395561	D 431 DALI O.A.	4010105395563

PEHA Elektro GmbH & Co.KG

a Honeywell Company
Daimlerstraße 4
58553 HALVER
DEUTSCHLAND

Tel.: 02353 9118 001
Fax: 02353 9118 311
mail: peha@honeywell.com
www.peha.de

Änderungen vorbehalten. © Honeywell PEHA