



The PTM 250 Radio Transmitter is a universal, extremely flat wireless switch insert with a maintenance-free energy generator.

This universal switch insert fits in numerous frame types from various installation material suppliers. The base plate can be glued or screwed into position for easy attachment to glass as well as plaster. Integration into the frame is similar to universal inserts for antenna sockets.

The switch insert is delivered without frame. Frames must be ordered separately from the desired manufacturer!

Notes	
Note	Additional technical data can be found in the datasheets assigned as download.

Technical data	
Radio technology	EnOcean 868 MHz, RPS type 2
Transmission range	300 m in open space, 30 m (typ.) within buildings
Antenna	Integrated EnOcean PTM 200 Radio Transmitter

Physical data	
Width	71 mm / 2.795 inches
Height	14 mm / 0.551 inches
Depth	71 mm / 2.795 inches

Material data	
Fire load	0 MJ
Weight	51.8 g

Environmental requirements	
Ambient temperature (operation)	-25 ... +65 °C
Relative humidity (without condensation)	95 %

Commercial data	
eCl@ss 10.0	27-14-42-01
eCl@ss 9.0	27-14-42-01
ETIM 8.0	EC001358
ETIM 7.0	EC001358
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454271633
Customs tariff number	85365080900

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

### Downloads

#### Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 758-940/001-000	<a href="#">↓</a>

### Documentation

System Description		
Radio Technology – General Product Information	pdf 493.44 KB	<a href="#">↓</a>

Bid Text			
758-940/001-000	19.02.2019	xml 4.18 KB	<a href="#">↓</a>
758-940/001-000	09.10.2017	doc 27.00 KB	<a href="#">↓</a>
ausschreiben.de 758-940/001-000			<a href="#">↓</a>

### CAD/CAE-Data

CAE data	
WSCAD Universe 758-940/001-000	<a href="#">↓</a>