



## Cable ties without serration in flexible TPU

The soft, flexible material makes these ties particularly suitable for use on sensitive wires, for instance fibre-optic cables. Additionally they are suitable for moving elements and vibrating applications. The double slotted head allows for parallel bundling.

### Features and benefits

- Elastic and flexible cable ties with rounded and smooth edges
- Releasable and reusable
- Double slotted head with fixation pawl
- Flexibility ensures steady and evenly distributed pressure
- Tight fixation even in vertical position: prevent sliding down or loosening bundle
- Suitable for moving elements and vibrating applications like windmills, machines, robotics, pulsating tubing and conduits
- Ideal use for temporarily fixation for presentations, concerts, theatres, exhibitions
- Long lifetime when used indoor
- Remains flexible even at cold temperatures (-20°C)




The elasticity of the SOFTIX ties makes them suitable for use in many applications.



SOFTIX ties available in small packaging units.



[www.HellermannTyton.com/Softfix-cat22](http://www.HellermannTyton.com/Softfix-cat22)



SRT- and SOFTFIX-Series

**i** With 2nd loop to run bundles in parallel!

### SRT-Series for industry quantities

| TYPE     | Width (W) | Length (L) | Bundle Ø max. |     | Material | Colour     | Pack Cont. | Article-No. |
|----------|-----------|------------|---------------|-----|----------|------------|------------|-------------|
| SRT1807  | 7.0       | 180.0      | 45.0          | 57  | TPU      | Black (BK) | 50 pcs.    | 115-07189   |
| SRT2607  | 7.0       | 260.0      | 70.0          | 57  | TPU      | Black (BK) | 50 pcs.    | 115-07269   |
| SRT26011 | 11.0      | 260.0      | 65.0          | 123 | TPU      | Black (BK) | 50 pcs.    | 115-11269   |
| SRT34011 | 11.0      | 340.0      | 90.0          | 123 | TPU      | Black (BK) | 50 pcs.    | 115-11349   |
| SRT58028 | 28.0      | 580.0      | 150.0         | 360 | TPU      | Black (BK) | 10 pcs.    | 115-28589   |
| SRT88028 | 28.0      | 880.0      | 240.0         | 360 | TPU      | Black (BK) | 180 pcs.   | 115-28889   |

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

### SOFTFIX-Family

| TYPE        | Width (W) | Length (L) | Bundle Ø max. |     | Material | Colour     | Pack Cont. | Article-No. |
|-------------|-----------|------------|---------------|-----|----------|------------|------------|-------------|
| SOFTFIX XS  | 7.0       | 180.0      | 45.0          | 57  | TPU      | Black (BK) | 16 pcs.    | 115-07190   |
| SOFTFIX S   | 7.0       | 260.0      | 70.0          | 57  | TPU      | Black (BK) | 12 pcs.    | 115-07270   |
| SOFTFIX M   | 11.0      | 260.0      | 65.0          | 123 | TPU      | Black (BK) | 8 pcs.     | 115-11270   |
| SOFTFIX L   | 11.0      | 340.0      | 90.0          | 123 | TPU      | Black (BK) | 6 pcs.     | 115-11350   |
| SOFTFIX XL  | 28.0      | 580.0      | 150.0         | 360 | TPU      | Black (BK) | 3 pcs.     | 115-28590   |
| SOFTFIX XXL | 28.0      | 880.0      | 240.0         | 360 | TPU      | Black (BK) | 3 pcs.     | 115-28898   |

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.



Add items to your watchlist!

[www.HT.click/9-75](http://www.HT.click/9-75)



## Material Specification Overview

| MATERIAL  | Material Shortcut | Operating Temperature                                | Colour**                 | Flammability | Material Properties*  | Material Specifications |
|---|-------------------|--|--------------------------|--------------|---|-------------------------|
| Aluminium alloy   | AL                | -40 °C to +180 °C                                    | Natural (NA)             |              | <ul style="list-style-type: none"> <li>Corrosion resistant</li> <li>Antimagnetic</li> </ul>   | RoHS                    |
| Chloroprene Rubber  | CR                | -20 °C to +80 °C                                     | Black (BK)               |              | <ul style="list-style-type: none"> <li>Weather resistant</li> <li>High yield strength</li> </ul>  | RoHS                    |
| Ethylene Tetrafluoroethylene (Tefzel®)                      | E/TFE             | -80 °C to +170 °C                                    | Blue (BU)                | UL 94 V0     | <ul style="list-style-type: none"> <li>Resistance to radioactivity</li> <li>UV resistant, not moisture sensitive</li> <li>Good chemical resistance to acids, bases, oxidizing agents</li> </ul>   | RoHS                    |
| Polyacetal  | POM               | -40 °C to +90 °C, (+110 °C, 500 h)                   | Natural (NA)             | UL 94 HB     | <ul style="list-style-type: none"> <li>Limited brittleness sensitivity</li> <li>Flexible at low temperature</li> <li>Not moisture sensitive</li> <li>Robust on impact</li> </ul>  | RoHS                    |
| Polyamide 11  | PA11              | -40 °C to +85 °C, (+105 °C, 500 h)                   | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Bio-plastic, derived from vegetable oil</li> <li>Strong impact resistance at low temperature</li> <li>Very low moisture absorption</li> <li>Weather resistant</li> <li>Good chemical resistance</li> </ul> | HF<br>RoHS              |
| Polyamide 12  | PA12              | -40 °C to +85 °C, (+105 °C, 500 h)                   | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Good chemical resistance to acids, bases, oxidizing agents</li> <li>UV resistant</li> </ul>  | HF<br>RoHS              |
| Polyamide 4.6   | PA46              | -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) | Natural (NA), Grey (GY)  | UL 94 V2     | <ul style="list-style-type: none"> <li>Resistance to high temperatures</li> <li>Very moisture sensitive</li> <li>Low smoke sensitivity</li> </ul>   | HF<br>LFH<br>RoHS       |
| Polyamide 6   | PA6               | -40 °C to +80 °C                                     | Black (BK)               | UL 94 V2     | <ul style="list-style-type: none"> <li>High yield strength</li> </ul>   | RoHS                    |
| Polyamide 6, high impact modified                           | PA6HIR            | -40 °C to +80 °C                                     | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Limited brittleness sensitivity</li> <li>Higher flexibility at low temperature</li> </ul>  | RoHS                    |
| Polyamide 6.6   | PA66              | -40 °C to +85 °C, (+105 °C, 500 h)                   | Black (BK), Natural (NA) | UL 94 V2     | <ul style="list-style-type: none"> <li>High yield strength</li> </ul>   | HF<br>RoHS              |
| Polyamide 6.6, glass-fibre reinforced                       | PA66GF13          | -40 °C to +105 °C                                    | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Good resistance to lubricants, fuels, salt water and solvents</li> </ul>   | HF<br>RoHS              |
| Polyamide 6.6, heat and UV-stabilised                       | PA66HSUV          | -40 °C to +105 °C                                    | Black (BK)               | UL 94 V2     | <ul style="list-style-type: none"> <li>High yield strength</li> <li>Modified elevated maximum temperature</li> <li>UV resistant</li> </ul>  | HF<br>RoHS              |
| Polyamide 6.6, heat stabilised                              | PA66HS            | -40 °C to +105 °C                                    | Black (BK), Natural (NA) | UL 94 V2     | <ul style="list-style-type: none"> <li>High yield strength</li> <li>Modified elevated maximum temperature</li> </ul>  | HF<br>RoHS              |
| Polyamide 6.6, high impact modified                         | PA66HIR           | -40 °C to +80 °C, (+105 °C, 500 h)                   | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Limited brittleness sensitivity</li> <li>Higher flexibility at low temperature</li> </ul>  | RoHS                    |
| Polyamide 6.6, high impact modified, heat and UV-stabilised | PA66HIRHSUV       | -40 °C to +110 °C                                    | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Limited brittleness sensitivity</li> <li>Higher flexibility at low temperature</li> <li>Modified elevated maximum temperature</li> <li>High yield strength, UV resistant</li> </ul>                        | RoHS                    |
| Polyamide 6.6, high impact modified, heat stabilised        | PA66HIRHS         | -40 °C to +105 °C                                    | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Limited brittleness sensitivity</li> <li>Higher flexibility at low temperature</li> <li>Modified elevated maximum temperature</li> </ul>   | RoHS                    |
| Polyamide 6.6, high impact modified, scan black)            | PA66HIR(S)        | -40 °C to +80 °C, (+105 °C, 500 h)                   | Black (BK)               | UL 94 HB     | <ul style="list-style-type: none"> <li>Limited brittleness sensitivity</li> <li>Higher flexibility at low temperature</li> </ul>  | RoHS                    |
| Polyamide 6.6, UV-resistant                                 | PA66W             | -40 °C to +85 °C, (+105 °C, 500 h)                   | Black (BK)               | UL 94 V2     | <ul style="list-style-type: none"> <li>High yield strength</li> <li>UV resistant</li> </ul>   | HF<br>RoHS              |

| MATERIAL  | Material Shortcut | Operating Temperature                 | Colour**                    | Flammability           | Material Properties*  | Material Specifications |
|---|-------------------|---------------------------------------|-----------------------------|------------------------|---|-------------------------|
| <b>Polyamide 6.6,</b><br>with metal particles   | PA66MP            | -40 °C to +85 °C,<br>(+105 °C, 500 h) | Blue (BU)                   | UL 94 HB               | • High yield strength<br>• Metal and X-Ray detectable   | HF<br>RoHS              |
| <b>Polyamide 6.6,</b><br>with metal particles   | PA66MP+           | -40 °C to +85 °C                      | Blue (BU)                   | not flame<br>retardant | • High yield strength<br>• Metal and X-Ray detectable   | HF<br>RoHS              |
| <b>Polyamide 6.6 V0</b>   | PA66V0            | -40 °C to +85 °C                      | White (WH)                  | UL 94 V0               | • High yield strength<br>• Low smoke emission   | HF<br>LFH<br>RoHS       |
| <b>Polyester</b>  | SP                | -50 °C to +150 °C                     | Black (BK)                  |                        | • UV resistant<br>• Good chemical resistance to most<br>acids, bases and oils   | HF<br>LFH<br>RoHS       |
| <b>Polyetheretherketone</b>   | PEEK              | -55 °C to +240 °C                     | Beige (BGE)                 | UL 94 V0               | • Resistance to radioactivity<br>• Not moisture sensitive<br>• Good chemical resistance to acids,<br>bases, oxidising agents  | HF<br>LFH<br>RoHS       |
| <b>Polyethylene</b>   | PE                | -40 °C to +50 °C                      | Black (BK),<br>Grey (GY)    | UL 94 HB               | • Low moisture absorption<br>• Good chemical resistance to most<br>acids, bases, alcohol, oils  | HF<br>RoHS              |
| <b>Polyolefin</b>   | PO                | -40 °C to +90 °C                      | Black (BK)                  | UL 94 V0               | • Low smoke emissions   | HF<br>LFH<br>RoHS       |
| <b>Polypropylene</b>  | PP                | -40 °C to +115 °C                     | Black (BK),<br>Natural (NA) | UL 94 HB               | • Floats in water<br>• Moderate yield strength<br>• Good chemical resistance to acids,<br>bases and solvents  | HF<br>RoHS              |
| <b>Polypropylene,<br/>Ethylene Propylene<br/>Diene Terpolymer</b><br>rubber free of Nitrosamine | PP, EPDM          | -20 °C to +95 °C                      | Black (BK)                  | UL 94 HB               | • Good resistance to high temperature<br>• Good chemical and abrasion<br>resistance   | HF<br>RoHS              |
| <b>Polypropylene</b><br>with metal particles  | PPMP              | -40 °C to +115 °C                     | Blue (BU)                   | UL 94 HB               | • Metal and X-Ray detectable<br>• Heat resistant<br>• Moderate yield strength<br>• Good chemical resistance   | RoHS                    |
| <b>Polypropylene</b><br>with metal particles  | PPMP+             | -40 °C to +85 °C                      | Blue (BU)                   | not flame<br>retardant | • High yield strength<br>• Metal and X-Ray detectable   | HF<br>RoHS              |
| <b>Polyvinylchloride</b>  | PVC               | -10 °C to +70 °C                      | Black (BK),<br>Natural (NA) | UL 94 V0               | • Low moisture absorption<br>• Good chemical resistance to acids,<br>bases, salts, alcohol, oils  | RoHS                    |
| <b>Stainless Steel,<br/>Stainless Steel</b>   | SS304, SS316      | -80 °C to +538 °C                     | Natural (NA)                | non-burning            | • Corrosion resistant<br>• Antimagnetic<br>• Weather resistant<br>• Chemical resistance<br>• SS316 also resistant against seawater,<br>salt spray and anorganic acids | HF<br>LFH<br>RoHS       |
| <b>Thermoplastic<br/>Polyurethane</b>   | TPU               | -40 °C to +85 °C                      | Black (BK)                  | UL 94 HB               | • High elasticity<br>• Good chemical resistance to acids,<br>bases and oxidising agents   | HF<br>RoHS              |

Tefzel® is a registered trademark of DuPont. General linguistic usage for cable ties made from raw material E/TFE is Tefzel®-Tie. In addition to Tefzel® from DuPont HellermannTyton also uses equivalent E/TFE raw material from other suppliers.

\*\*Further colours available on request.

\*These details are only guide values. They should not be regarded as an exhaustive material specification and are no substitute for suitability tests. Please see our datasheets for further details.



**Minimum Loop Tensile Strength  
for Cable Ties (newton)**

HF = Halogenfree

LFH = Limited Fire Hazard

RoHS = Restriction of Hazardous Substances