



1-piece fixing ties with arrowhead, with disc, sealed

1-piece fixing ties with arrowhead, with disc, for round holes, sealed


The parts are mainly used in the automotive industry. This fastening solution is used to secure cable harnesses e.g. in car doors. We offer a variety of panel thicknesses and hole sizes to suit all kinds of application. The seal protects the interior and surrounding cables among other things from splash water.

Features and benefits

- One-piece fixing ties with cellular rubber disc
- Especially suitable for door and tailgate harnesses used for car body applications
- Made from PA66 heat-stabilised material
- Cellular rubber disc minimises ingress of dust, dirt and splash water



The additional seal protects against the ingress of moisture.



One piece fixing tie with arrowhead and disc, standard design

| TYPE | Drawing | Hole Ø (FH) | Panel Thickness | Width (W) | Length (L) | Bundle Ø max. | | Disc Ø | Material | Colour | Tools | Article-No. |
|---------------------------------|-----------|--|-----------------|-----------|------------|---------------|------|--------|--------------|--------------|--------------|-------------|
| T50SOSS FT6.5E-MS-MD | | 6.25 - 6.75, 6.1 - 6.6 (hexagonal) | 0.7 - 1.6 | 4.6 | 163.0 | 35.0 | 180 | 16.0 | PA66HS | Natural (NA) | 2-3;5-6;8;10 | 126-00065 |
| T50XROSS FT6.5-E-MDL | | 6.25 - 6.75, 6.1 - 6.6 (hexagonal) | 1.2 - 2.1 | 4.6 | 200.0 | 45.0 | 200 | 16.0 | PA66HS | Black (BK) | 2-3;5-6;8;10 | 156-00379 |
| T50SOSS FT6.5E-MDL | | 6.3 - 6.7 | 0.6 - 1.8 | 4.6 | 158.8 | 30.0 | 225 | 16.0 | PA66HS | Green (GN) | 2-3;5-6;8;10 | 126-03100 |
| | 6.3 - 6.7 | 0.6 - 1.8 | 4.6 | 158.8 | 30.0 | 225 | 16.0 | PA66HS | Black (BK) | 2-3;5-6;8;10 | 156-00264 | |
| | 6.3 - 6.7 | 0.6 - 1.8 | 4.6 | 158.8 | 30.0 | 225 | 16.0 | PA66HS | Natural (NA) | 2-3;5-6;8;10 | 156-00271 | |

All dimensions in mm. Subject to technical changes.

| Recommended Tools | | | | | | |
|-------------------|------|------|----------|------|------|------|
| | 2 | 3 | 5 | 6 | 8 | 10 |
| | MK20 | MK21 | MK3PNSP2 | EVO7 | MK7P | EVO9 |
| | 549 | 549 | 550 | 552 | 554 | 553 |

For more information on toolings please refer to the Application Tooling chapter.



Material Specification Overview

| MATERIAL | Material Shortcut | Operating Temperature | Colour** | Flammability | Material Properties* | Material Specifications |
|---|-------------------|--|--------------------------|--------------|---|-------------------------|
| Aluminium alloy | AL | -40 °C to +180 °C | Natural (NA) | | <ul style="list-style-type: none"> Corrosion resistant Antimagnetic | RoHS |
| Chloroprene Rubber | CR | -20 °C to +80 °C | Black (BK) | | <ul style="list-style-type: none"> Weather resistant High yield strength | RoHS |
| Ethylene Tetrafluoroethylene (Tefzel®) | E/TFE | -80 °C to +170 °C | Blue (BU) | UL 94 V0 | <ul style="list-style-type: none"> Resistance to radioactivity UV resistant, not moisture sensitive Good chemical resistance to acids, bases, oxidizing agents | RoHS |
| Polyacetal | POM | -40 °C to +90 °C, (+110 °C, 500 h) | Natural (NA) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Flexible at low temperature Not moisture sensitive Robust on impact | RoHS |
| Polyamide 11 | PA11 | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Bio-plastic, derived from vegetable oil Strong impact resistance at low temperature Very low moisture absorption Weather resistant Good chemical resistance | HF RoHS |
| Polyamide 12 | PA12 | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Good chemical resistance to acids, bases, oxidizing agents UV resistant | HF RoHS |
| Polyamide 4.6 | PA46 | -40 °C to +130 °C, (+150 °C, 5000 h; +195 °C, 500 h) | Natural (NA), Grey (GY) | UL 94 V2 | <ul style="list-style-type: none"> Resistance to high temperatures Very moisture sensitive Low smoke sensitivity | HF LFH RoHS |
| Polyamide 6 | PA6 | -40 °C to +80 °C | Black (BK) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength | RoHS |
| Polyamide 6, high impact modified | PA6HIR | -40 °C to +80 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature | RoHS |
| Polyamide 6.6 | PA66 | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK), Natural (NA) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength | HF RoHS |
| Polyamide 6.6, glass-fibre reinforced | PA66GF13 | -40 °C to +105 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Good resistance to lubricants, fuels, salt water and solvents | HF RoHS |
| Polyamide 6.6, heat and UV-stabilised | PA66HSUV | -40 °C to +105 °C | Black (BK) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength Modified elevated maximum temperature UV resistant | HF RoHS |
| Polyamide 6.6, heat stabilised | PA66HS | -40 °C to +105 °C | Black (BK), Natural (NA) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength Modified elevated maximum temperature | HF RoHS |
| Polyamide 6.6, high impact modified | PA66HIR | -40 °C to +80 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature | RoHS |
| Polyamide 6.6, high impact modified, heat and UV-stabilised | PA66HIRHSUV | -40 °C to +110 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature Modified elevated maximum temperature High yield strength, UV resistant | RoHS |
| Polyamide 6.6, high impact modified, heat stabilised | PA66HIRHS | -40 °C to +105 °C | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature Modified elevated maximum temperature | RoHS |
| Polyamide 6.6, high impact modified, scan black) | PA66HIR(S) | -40 °C to +80 °C, (+105 °C, 500 h) | Black (BK) | UL 94 HB | <ul style="list-style-type: none"> Limited brittleness sensitivity Higher flexibility at low temperature | RoHS |
| Polyamide 6.6, UV-resistant | PA66W | -40 °C to +85 °C, (+105 °C, 500 h) | Black (BK) | UL 94 V2 | <ul style="list-style-type: none"> High yield strength UV resistant | HF RoHS |

| MATERIAL | Material Shortcut | Operating Temperature | Colour** | Flammability | Material Properties* | Material Specifications |
|---|-------------------|---------------------------------------|-----------------------------|------------------------|---|-------------------------|
| Polyamide 6.6, with metal particles | PA66MP | -40 °C to +85 °C, (+105 °C, 500 h) | Blue (BU) | UL 94 HB | • High yield strength • Metal and X-Ray detectable | HF RoHS |
| Polyamide 6.6, with metal particles | PA66MP+ | -40 °C to +85 °C | Blue (BU) | not flame retardant | • High yield strength • Metal and X-Ray detectable | HF RoHS |
| Polyamide 6.6 V0 | PA66V0 | -40 °C to +85 °C | White (WH) | UL 94 V0 | • High yield strength • Low smoke emission | HF LFH RoHS |
| Polyester | SP | -50 °C to +150 °C | Black (BK) | | • UV resistant • Good chemical resistance to most acids, bases and oils | HF LFH RoHS |
| Polyetheretherketone | PEEK | -55 °C to +240 °C | Beige (BGE) | UL 94 V0 | • Resistance to radioactivity • Not moisture sensitive • Good chemical resistance to acids, bases, oxidising agents | HF LFH RoHS |
| Polyethylene | PE | -40 °C to +50 °C | Black (BK), Grey (GY) | UL 94 HB | • Low moisture absorption • Good chemical resistance to most acids, bases, alcohol, oils | HF RoHS |
| Polyolefin | PO | -40 °C to +90 °C | Black (BK) | UL 94 V0 | • Low smoke emissions | HF LFH RoHS |
| Polypropylene | PP | -40 °C to +115 °C | Black (BK), Natural (NA) | UL 94 HB | • Floats in water • Moderate yield strength • Good chemical resistance to acids, bases and solvents | HF RoHS |
| Polypropylene, Ethylene Propylene Diene Terpolymer rubber free of Nitrosamine | PP, EPDM | -20 °C to +95 °C | Black (BK) | UL 94 HB | • Good resistance to high temperature • Good chemical and abrasion resistance | HF RoHS |
| Polypropylene with metal particles | PPMP | -40 °C to +115 °C | Blue (BU) | UL 94 HB | • Metal and X-Ray detectable • Heat resistant • Moderate yield strength • Good chemical resistance | RoHS |
| Polypropylene with metal particles | PPMP+ | -40 °C to +85 °C | Blue (BU) | not flame retardant | • High yield strength • Metal and X-Ray detectable | HF RoHS |
| Polyvinylchloride | PVC | -10 °C to +70 °C | Black (BK), Natural (NA) | UL 94 V0 | • Low moisture absorption • Good chemical resistance to acids, bases, salts, alcohol, oils | RoHS |
| Stainless Steel, Stainless Steel | SS304, SS316 | -80 °C to +538 °C | Natural (NA) | non-burning | • Corrosion resistant • Antimagnetic • Weather resistant • Chemical resistance • SS316 also resistant against seawater, salt spray and anorganic acids | HF LFH RoHS |
| Thermoplastic Polyurethane | TPU | -40 °C to +85 °C | Black (BK) | UL 94 HB | • High elasticity • Good chemical resistance to acids, bases and oxidising agents | HF RoHS |

Tefzel® is a registered trademark of DuPont. General linguistic usage for cable ties made from raw material E/TFE is Tefzel®-Tie. In addition to Tefzel® from DuPont HellermannTyton also uses equivalent E/TFE raw material from other suppliers.

**Further colours available on request.

*These details are only guide values. They should not be regarded as an exhaustive material specification and are no substitute for suitability tests. Please see our datasheets for further details.



= Minimum Loop Tensile Strength
for Cable Ties (newton)

HF = Halogenfree

LFH = Limited Fire Hazard

RoHS = Restriction of Hazardous Substances