

Shrinkable markers "Ladder Style", thermal transfer

TLFX DS – 2:1 Rail Limited Fire Hazard "Ladder Style"

TLFX DS is a halogen free European rail approved 2:1 heat shrink marker material supplied pre-cut and formatted into a convenient "ladder" system. Special material properties show low smoke propagation, density and toxicity. This pre-cut format not only allows printing on both sides of the marker but the user can also easily choose and pick each required marker. Special material properties show low smoke propagation, density and toxicity. The tubing has been especially prepared so that the print performance is excellent at all times using HellermannTyton's printer range.

Features and benefits

- Shrink ratio 2:1
- Halogen Free
- Low smoke propagation, density and toxicity
- 50 mm, 25 mm and 16 mm pre-cut marker options as standard, other lengths available on request
- Available in yellow or white
- Cable range 38.1 mm to 1.2 mm
- Delivery in convenient storage boxes



Shrinkable rail approved markers TLFX DS.

MATERIAL	Polyolefin, cross-linked (PO-X)
Operating Temperature	-55 °C to +105 °C
Min. Shrink Temperature	+100 °C
Shrink Ratio	2:1
Recommended Ribbon Type	TTDTHOUT
Thermal Transfer Printer	TT431, TT4030, TrakMark DS
EN 45545-2 Classification	R22 HL3, R23 HL3



For size matrix please refer to page 452.



HF ✓

LFH ✓

RoHS ✓

TYPE	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Pack Cont.	Colour	Article-No.
TLFX24DS-2x25WH	2.4	1.2	25.0	0.52	10,000 pcs.	White (WH)	553-60020
TLFX24DS-2x25YE	2.4	1.2	25.0	0.52	10,000 pcs.	Yellow (YE)	553-60029
TLFX24DS-1x50WH	2.4	1.2	50.0	0.52	5,000 pcs.	White (WH)	553-60000
TLFX24DS-1x50YE	2.4	1.2	50.0	0.52	5,000 pcs.	Yellow (YE)	553-60010
TLFX32DS-2x25WH	3.2	1.6	25.0	0.64	10,000 pcs.	White (WH)	553-60021
TLFX32DS-2x25YE	3.2	1.6	25.0	0.64	10,000 pcs.	Yellow (YE)	553-60030
TLFX32DS-1x50WH	3.2	1.6	50.0	0.64	5,000 pcs.	White (WH)	553-60001
TLFX32DS-1x50YE	3.2	1.6	50.0	0.64	5,000 pcs.	Yellow (YE)	553-60011
TLFX48DS-2x25WH	4.8	2.4	25.0	0.64	10,000 pcs.	White (WH)	553-60022
TLFX48DS-2x25YE	4.8	2.4	25.0	0.64	10,000 pcs.	Yellow (YE)	553-60031
TLFX48DS-1x50WH	4.8	2.4	50.0	0.64	5,000 pcs.	White (WH)	553-60002
TLFX48DS-1x50YE	4.8	2.4	50.0	0.64	5,000 pcs.	Yellow (YE)	553-60012
TLFX64DS-2x25WH	6.4	3.2	25.0	0.73	6,000 pcs.	White (WH)	553-60023
TLFX64DS-2x25YE	6.4	3.2	25.0	0.73	6,000 pcs.	Yellow (YE)	553-60032
TLFX64DS-1x50WH	6.4	3.2	50.0	0.73	3,000 pcs.	White (WH)	553-60003
TLFX64DS-1x50YE	6.4	3.2	50.0	0.73	3,000 pcs.	Yellow (YE)	553-60013

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

EN 45545-2

ASTM

For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!


www.HT.click/9-469





Shrinkable markers "Ladder Style", thermal transfer

TLFX DS – 2:1 Rail Limited Fire Hazard "Ladder Style"



TYPE	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Pack Cont.	Colour	Article-No.
TLFX95DS-2x25WH	9.5	4.8	25.0	0.70	5,000 pcs.	White (WH)	553-60024
TLFX95DS-2x25YE	9.5	4.8	25.0	0.70	5,000 pcs.	Yellow (YE)	553-60033
TLFX95DS-1x50WH	9.5	4.8	50.0	0.70	2,500 pcs.	White (WH)	553-60004
TLFX95DS-1x50YE	9.5	4.8	50.0	0.70	2,500 pcs.	Yellow (YE)	553-60014
TLFX127DS-2x25WH	12.7	6.4	25.0	0.70	3,000 pcs.	White (WH)	553-60025
TLFX127DS-2x25YE	12.7	6.4	25.0	0.70	3,000 pcs.	Yellow (YE)	553-60034
TLFX127DS-1x50WH	12.7	6.4	50.0	0.70	1,500 pcs.	White (WH)	553-60005
TLFX127DS-1x50YE	12.7	6.4	50.0	0.70	1,500 pcs.	Yellow (YE)	553-60015
TLFX190DS-2x25WH	19.0	9.5	25.0	0.78	3,000 pcs.	White (WH)	553-60026
TLFX190DS-2x25YE	19.0	9.5	25.0	0.78	3,000 pcs.	Yellow (YE)	553-60035
TLFX190DS-1x50WH	19.0	9.5	50.0	0.78	1,500 pcs.	White (WH)	553-60006
TLFX190DS-1x50YE	19.0	9.5	50.0	0.78	1,500 pcs.	Yellow (YE)	553-60016
TLFX254DS-2x25WH	25.4	12.7	25.0	0.93	2,000 pcs.	White (WH)	553-60027
TLFX254DS-2x25YE	25.4	12.7	25.0	0.93	2,000 pcs.	Yellow (YE)	553-60036
TLFX254DS-1x50WH	25.4	12.7	50.0	0.93	1,000 pcs.	White (WH)	553-60007
TLFX254DS-1x50YE	25.4	12.7	50.0	0.93	1,000 pcs.	Yellow (YE)	553-60017
TLFX381DS-2x25WH	38.1	19.1	25.0	0.98	1,000 pcs.	White (WH)	553-60028
TLFX381DS-2x25YE	38.1	19.1	25.0	0.98	1,000 pcs.	Yellow (YE)	553-60037
TLFX381DS-1x50WH	38.1	19.1	50.0	0.98	500 pcs.	White (WH)	553-60008
TLFX381DS-1x50YE	38.1	19.1	50.0	0.98	500 pcs.	Yellow (YE)	553-60018

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

EN 45545-2

ASTM

For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!

www.HT.click/9-470

