



### Manual tensioning tool for metal ties MST-Series

#### MST6 for 5.9 mm strap width

The MST6 tool has been specially developed for reliably applying HellermannTyton metal cable ties of the MST-S series. Due to the punch-lock mechanism the tie is mechanically crimped and leads to metal deformation of the tie ends. This punch-lock mechanism ensures a reliable bundling with perfect resistance to vibration. The tension force is freely adjustable by the operator.

#### Features and benefits

- Tough metal tool
- Ergonomic design
- Consistent tensioning and automatically cutting of metal ties
- Designed for use with MST-S Series ties (5.9 mm)
- For tensioning, fixing and cutting MST-S metal ties only



MST6.



[www.HellermannTyton.com/MST6-cat22](http://www.HellermannTyton.com/MST6-cat22)

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MST6	MST6	5.9	0.3	0.532 kg	110-61000
SP MST6 replacement blade	Replacement Blade	-	-	0.003 kg	110-61001
SP MST6 replacement punch	Replacement Punch	-	-	0.001 kg	110-61002

All dimensions in mm. Subject to technical changes.

### Manual tensioning tool for metal ties MST-Series

#### MST9 for 8.9 mm strap width

The MST9 tool has been specially developed for reliably applying HellermannTyton metal cable ties of the MST-M series. Due to the punch-lock mechanism the tie is mechanically crimped and leads to metal deformation of the tie ends. This punch-lock mechanism ensures a reliable bundling with perfect resistance to vibration. The tension force is freely adjustable by the operator.

#### Features and benefits

- Tough metal tool
- Ergonomic design
- Consistent tensioning and automatic cutting of metal ties
- Designed for use with MST-M Series ties (8.9 mm)
- For tensioning, fixing and cutting MST-M metal ties only



MST9.

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
MST9	MST9	8.9	0.4	0.532 kg	110-13000
SP MST9 replacement blade	Replacement Blade	-	-	0.004 kg	110-13001
SP MST9 replacement punch	Replacement Punch	-	-	0.001 kg	110-13002

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!  
[www.HT.click/9-559](http://www.HT.click/9-559)

