

Product data sheet

Item No. 92.207.2060.1

Cable assembly GST1814KSBS 15H 20SW

geis® Extension cable female - male; length: 2m; type GST1814; 4-pole; 250/400 V / 16 A; colour of coding: black with black strain-relief; cable: H05Z1Z1-F 4G1,5, colour: black



Item No.	92.207.2060.1
EAN	4015573620155
Order Unit	25 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	4
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Cable type	H05Z1Z1-F
Cable colour	Black
Cable diameter	9.2 mm
Version of cable	Female - male

Type of cord set	Connecting cable
Version cable end 1	GST18i4 socket
Version cable end 2	GST18i4 plug

Material

Surface finish	Tin-plated
Halogen free	Yes
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

Pol/pole Aderfarbe/colour of core

L1	braun/brown
⊕	grün-gelb/green-yellow
N	blau/blue
L2	schwarz/black

.F	Farbe colour	Codierung *x* Buchse female	Codierung *y* Stecker male	Kabelfarbe / cable colour Zugentlastungsfarbe/strain relief colour
.1	schwarz black	2 N PE 1	1 PE N 2	schwarz black
.2	weiß white	2 N PE 1	1 PE N 2	weiß white
.3	grau grey	2 N PE 1	1 PE N 2	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.207.XX60.F	XX in dm-Schritten	92.207.1060.1 = 10dm/L= 1000mm	GST1814KSBS 15H 10SW
U2.207.XX60.F	XX in m-Schritten	U2.207.1260.1 = 12 m/L=12000mm	GST1814KSBS 15H X10SW

Weitere Daten siehe Katalog further data see catalog

Typ/type: GST1814KSBS 15H. SW = schwarz/black, WS = weiß/white, GR01 = grau/grey

PRE-ASSEMBLED CABLE KONFEKT-LEITUNG
 Buchse/female-Stecker/male HALOGEN-FREE
 Schraubanschluss/screw connection 1,5mm 250V