

## Product data sheet

Item No. 92.208.0564.1

### Cable assembly

geis® Connection cable male - free end; length: 0,5m; type GST18I4; 4-pole; 250/400 V / 20 A; colour of coding: black with black strain-relief; cable: H05Z1Z1-F 4G2,5, colour: black



|            |               |
|------------|---------------|
| Item No.   | 92.208.0564.1 |
| EAN        | 4049088121487 |
| Order Unit | 75 Piece(s)   |

### Certificates / Approvals



### Technical data

#### General

|  |        |
|--|--------|
| Rated current                            | 20 A   |
| Rated voltage                            | 400 V  |
| Rated impulse voltage                    | 4 kV   |
| Pollution degree                         | 2      |
| Mechanical coding                        | Code 1 |
| Interlockable                            | Yes    |
| Color of coding/ contact carrier         | Black  |
| Marking of poles                         |        |
| Color of housing inclusive strain relief | Black  |

#### Model

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Number of poles                 | 4                                   |
| Nominal cross section conductor | 2.5 mm <sup>2</sup>                 |
| Degree of protection (IP)       | IP40                                |
| Wire strip length               | 10 mm                               |
| sheath strip length             | 35 mm                               |
| Preparation of conductor ends   | Ultrasonically compressed wire ends |
| Cable type                      | H05Z1Z1-F                           |

|                     |                  |
|---------------------|------------------|
| Cable colour        | Black            |
| Cable diameter      | 10.8 mm          |
| Version of cable    | Male - free end  |
| Type of cord set    | Connection cable |
| Version cable end 1 | GST18i4 plug     |
| Version cable end 2 | Free end         |

**Material**

|  |            |
|--|------------|
| Surface finish                               | Tin-plated |
| Halogen free                                 | Yes        |
| Continuous temperature of cable              | 70 °C      |
| Insulation components continuous temperature | 100 °C     |

**Dimensions**

|              |       |
|--------------|-------|
| Total length | 0.5 m |
|--------------|-------|