

Product data sheet

Item No. 92.208.6060.1

Cable assembly GST1814KSBS 25H 60SW

geis® Extension cable female - male; length: 6m; type GST1814; 4-pole; 250/400 V / 20 A; colour of coding: black with black strain-relief; cable: H05Z1Z1-F 4G2,5, colour: black



| | |
|------------|---------------|
| Item No. | 92.208.6060.1 |
| EAN | 4049644006333 |
| Order Unit | 8 Piece(s) |

Certificates / Approvals



Technical data

General

| | |
|--|--------|
| Rated current | 20 A |
| Rated voltage | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 1 |
| Interlockable | Yes |
| Color of coding/ contact carrier | Black |
| Marking of poles | |
| Color of housing inclusive strain relief | Black |

Model

| | |
|---------------------------------|---------------------|
| Number of poles | 4 |
| Nominal cross section conductor | 2.5 mm ² |
| Degree of protection (IP) | IP40 |
| Cable type | H05Z1Z1-F |
| Cable colour | Black |
| Cable diameter | 10.8 mm |
| Version of cable | Female - male |

| | |
|---------------------|------------------|
| Type of cord set | Connecting cable |
| Version cable end 1 | GST18i4 socket |
| Version cable end 2 | GST18i4 plug |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | Yes |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |

Dimensions

| | |
|--------------|-----|
| Total length | 6 m |
|--------------|-----|