

Product data sheet

Item No. 92.208.7064.1

Cable assembly GST1814KS-S 25H 70SW

geis® Connection cable male - free end; length: 7m; type GST1814; 4-pole; 250/400 V / 20 A; colour of coding: black with black strain-relief; cable: H05Z1Z1-F 4G2,5, colour: black



| | |
|------------|---------------|
| Item No. | 92.208.7064.1 |
| EAN | 4049644006647 |
| Order Unit | 5 Piece(s) |

Certificates / Approvals



Technical data

General

| | |
|--|--------|
| Rated current | 20 A |
| Rated voltage | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 1 |
| Interlockable | Yes |
| Color of coding/ contact carrier | Black |
| Marking of poles | |
| Color of housing inclusive strain relief | Black |

Model

| | |
|---------------------------------|-------------------------------------|
| Number of poles | 4 |
| Nominal cross section conductor | 2.5 mm ² |
| Degree of protection (IP) | IP40 |
| Wire strip length | 10 mm |
| sheath strip length | 35 mm |
| Preparation of conductor ends | Ultrasonically compressed wire ends |
| Cable type | H05Z1Z1-F |

| | |
|---------------------|------------------|
| Cable colour | Black |
| Cable diameter | 10.8 mm |
| Version of cable | Male - free end |
| Type of cord set | Connection cable |
| Version cable end 1 | GST18i4 plug |
| Version cable end 2 | Free end |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | Yes |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |

Dimensions

| | |
|--------------|-----|
| Total length | 7 m |
|--------------|-----|