Permanent Light 815 / Bulb Bulb 7W BA15D 115V



Part No.: 955.015.37

| MECHANICAL DATA | |
|------------------------------|--------------------------------|
| Height | 54 mm |
| Diameter | 16 mm |
| Housing colour | Silver |
| Weight with packaging | 9 g |
| Product weight | 9 g |
| ELECTRICAL DATA | |
| Operating voltage | 115V |
| Operating voltage frequency | 60Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 115 VAC |
| Rated operational current | 61 mA |
| Rated inrush current | 610 mA |
| Power illuminant | 7 W |
| OPTICAL DATA | |
| Lamp fitting/socket | BA15d |
| APPROVAL DATA | |
| Conforms with CE | No |
| Conforms with RoHS directive | Fulfills substance restriction |
| WEEE | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |

Pror additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.