

PRODUCT DATASHEET

OT 50/120...277/1A2 2DIMLT2 P

OT 2DIM IP64 | 0...10 V, AstroDIM – constant current LED drivers



Areas of application

- Street and urban lighting
- Industry
- Suitable for luminaires of protection classes I and II

Product benefits

- 2DIM functionality in one device (AstroDIM, 0...10 V)
- High surge protection: up to 6 kV (in protection class I or II)
- Fast programming without mains voltage
- High efficiency
- Great flexibility due to wide operating temperature range of -40...55 °C
- Protection through double isolation between mains input and LED output
- IP rating: IP64

Product features

- Available with different wattage: 50 W, 100 W, 110 W
- Input voltage: 120...277 V
- Available with output current range: up to 1,400 mA
- Flexible current setting with one additional wire (LEDset2)
- AstroDIM for autonomous dimming with five independent levels (astro mode)
- Isolated 0...10 V interface for unidirectional telemanagement systems
- Constant Lumen Output (CLO)

– Overtemperature protection with external NTC or LEDset2 interface

TECHNICAL DATA

Electrical data

| | |
|--|---------------------------|
| Nominal wattage | 50.00 W |
| Nominal output power | 50 W ¹⁾ |
| Nominal voltage | 120...277 V |
| Nominal output voltage | 20...55 V |
| Input voltage AC | 108...305 V ²⁾ |
| U-OUT (working voltage) | 60 V |
| Nominal current | 0.26 A ³⁾ |
| Nominal output current | 600...1250 mA |
| Inrush current | 30 A ⁴⁾ |
| Output current tolerance | ±5 % ⁵⁾ |
| Output ripple current (100 Hz) | 30 % |
| Mains frequency | 50/60 Hz |
| Total harmonic distortion | 15 % ⁶⁾ |
| Power factor λ | 0.95 ⁷⁾ |
| ECG efficiency | 86 % ⁸⁾ |
| Device power loss | 9.6 W ⁹⁾ |
| Max. ECG no. on circuit breaker 10 A (B) | 11 ¹⁰⁾ |
| Max. ECG no. on circuit breaker 16 A (B) | 17 ¹⁰⁾ |
| Max. ECG no. on circuit breaker 25 A (B) | 28 ¹⁰⁾ |
| Surge capability (L/N-Ground) | 6 kV ¹¹⁾ |
| Surge capability (L-N) | 6 kV ¹²⁾ |
| Galvanic isolation | SELV |
| Flickering metric (Pst LM) | ≤1 |

1) Partial load 12...50 W / Not dimmed

2) Permitted voltage range

3) 0.50 A for 120 V_{AC} / At 230 V

4) $t_{width} = 250 \mu s$ (measured at 50 % I_{peak})

5) Within nominal output current range

6) Max. output power at 230 V_{AC}

7) Minimum/Full load at 230 V/Half load at 230 V

8) At full load, default current and 230 V

9) Maximum

10) Type B

11) EQUI @ 12 Ohm acc. to EN 61547

12) @ 2 Ohm, acc. to EN61547

Photometrical data

| | |
|---------------------------------|------|
| Flickering metric (Pst LM) | ≤1 |
| Stroboscope effect metric (SVM) | ≤0.4 |

Dimensions & Weight

| | |
|--------------------------------------|-----------|
| Length | 168.00 mm |
| Mounting hole spacing, length | 152,0 mm |
| Width | 50.00 mm |
| Height | 30.00 mm |
| Wire preparation length, input side | 10 mm |
| Wire preparation length, output side | 10 mm |
| Product weight | 490.00 g |

Colors & materials

| | |
|-----------------|-------|
| Casing material | Metal |
| Body material | Metal |

Temperatures & operating conditions

| | |
|--|----------------------------|
| Ambient temperature range | -40...+55 °C ¹⁾ |
| Maximum temperature at tc test point | 80 °C ²⁾ |
| Max.housing temperature in case of fault | 120 °C |
| Permitted rel. humidity during operation | 5...85 % ³⁾ |

1) $T_{a(max)}=50^{\circ}\text{C}$ for input voltage 120/277V_{AC}

2) Maximum at the T_c-point

3) Non condensing, absolute humidity: 36g/m³

Lifespan

| | |
|--------------|-----------------------|
| ECG lifetime | 80000 h ¹⁾ |
|--------------|-----------------------|

1) At T_{case} = 70°C at T_c point / 10% failure rate

Additional product data

| | |
|----------------|--|
| Encapsulated | Yes |
| Product remark | No on/off switching of lamps possible via 0...10 V interface |

Capabilities

| | |
|------------------------|----------------------------|
| Dimmable | Yes |
| Dimming interface | 2DIM / 1...10 V / AstroDIM |
| Dimming range | 30...100 % |
| Overheating protection | Yes |
| Overload protection | Automatic reversible |

| | |
|--|--------|
| No-load proof | Yes |
| Short-circuit protection | Yes |
| Max. cable length to lamp/LED module | 10 m |
| Suitable for fixtures with prot. class | I / II |
| Type of connection, output side | Wires |

Certificates & Standards

| | |
|---------------------------|--|
| Approval marks – approval | CE / ENEC 15 / UR / CQC |
| Standards | Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 62384 / Acc. to EN 55015:2006 + A1:2007 + A2:2009 / Acc. to EN 61547 / Acc. to FCC 47 part 15 class A / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / UL-8750 |
| Protection class | I/II |
| Type of protection | IP64 |

LOGISTICAL DATA

| | |
|------------------------------|-------------|
| Temperature range at storage | -25...80 °C |
|------------------------------|-------------|

EQUIPMENT / ACCESSORIES

- OT Programmer hardware for configuration of 2DIM ECGs necessary
- Programmable via Tuner4TRONIC software


ADDITIONAL PRODUCT INFORMATION

- 800 mA type: Default output current is 700 mA without any resistor connected to the LEDset port.
- 1250 mA type: Default output current is 1000 mA without any resistor connected to the LEDset port.
- 1400 mA type: Default output current is 1000 mA without any resistor connected to the LEDset port.
- The LEDset2 interface is disabled by default and needs to be activated by the programming software. In this case the LEDset2 interface is activated the external thermal protection feature is disabled.
- The driver withstands an input voltage of up to 350 Vac for a maximum of two hours.
- The driver may shut down the load if the input voltage of the load is below the allowed minimum output voltage until the short circuit is removed or the correct load is connected and a power off/on cycle is performed.
- In case the input voltage of the load exceeds the output voltage range of the driver, it automatically reduces the output current to keep the output voltage controlled to the maximum allowed output voltage.
- The driver automatically reduces the output current in case the maximum allowed output power is exceeded, as long as the input voltage of the load is within the declared output voltage range of the driver. In all other cases the driver may shut down the load.
- The driver may shut down in case no load is connected to the driver output until the correct load is connected and a power off/on cycle is performed. Hot-plug of the load or external switching on the secondary side is not allowed.
- The EQUI (housing) shall be connected to the heat sink of the LED module to improve the surge withstand capability of the system and EMI in critical luminaires.
- By default the LEDset / NTCset / Prog+ port is set as NTCset port in resistor based mode with following values: start derating: 6.3 kOhm, end derating 5.0 kOhm, derating level 50 %.
- The default dimming mode is 0...10 V, AstroDIM-PD is disabled.- 0...10 V: 30 % minimum dimming level
- The constant lumen feature is disabled by default.
- If any output level is below the physical min level, the physical min level will be used.
- Dimming down to 14 % of the maximum rated output current could be enabled through the programming software, but the compliance with EN 61000-3-2 must be checked below 30 %.
- The driver is intended for built-in use. The luminaire manufacturer is responsible to prevent direct exposure for example to sunlight, water, snow,

ice.

- Time to reach the set output current upon start-up is less than 4 s.
- Programming of the driver via Prog+ and Prog- is only allowed without powering it via L/N.
- For further details please consult the 2DIMLT2 application guide.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|--|
|  | User instruction / safety instructions | 615706_Instruction sheet OT 50 1A2 2DIMLT2 P |
|  | Declarations of conformity | 646953_CB ENEC Information |
|  | Declarations of conformity | 725761_Certificate of analysis OT50 |
|  | Declarations of conformity | OT 2DIMLT2P CE 3676115 211119 |
|  | Declarations of conformity | 545682_EC-Conformity OT 50/120-277/xxx 2DIMLT2 P |
|  | Declarations of conformity | 612485_UL Conformity OT 50/120_277/xxx 2DIMLT2 P |
|  | Certificates | OT 50 2DIMLT2P CB DK91 169UL 080120 |
|  | Certificates | 617035_CCC Certificate OT 50/120-277/xxx 2DIMLT2 P |
|  | Certificates | 600316_CB certificate OT 50 2DIMLT2 E |
|  | Certificates | 600317_ENEC certificate OT 2DIMLT2 P |
|  | Certificates | OT 50 2DIMLT2P ENEC 01112 080120 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4052899173804 | Unpacked 1 | | 490.00 g | |
| 4052899173811 | Shipping box 20 | 368 mm x 338 mm x 85 mm | 10492.00 g | 10.57 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

