

TECHNICAL DATA

Electrical data

Nominal wattage	108.00 W
Nominal voltage	230...240 V
Nominal output voltage	11.6 V / 11.4 V ¹⁾
Input voltage range	230...240 V
Input voltage DC	176...275 V
Inrush current	0.6 A
Mains frequency	50/60 Hz ²⁾
Power factor λ	0.95 ³⁾
Device power loss	6 W ⁴⁾
Max. ECG no. on circuit breaker 10 A (B)	23
Max. ECG no. on circuit breaker 16 A (B)	38
Operating frequency	40 kHz


1) 105 W / 35 W

2) Approximately

3) Minimum

4) Maximum

Dimensions & Weight



Length	170.00 mm
Mounting hole spacing, length	140,0 mm
Width	44.00 mm
Height	34.00 mm
Wire preparation length, input side	8.0 mm
Wire preparation length, output side	8.0 mm
Product weight	160.00 g

Colors & materials

Product color	Grey
Casing material	Plastic

Body material	Plastic
---------------	---------

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	100 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Additional product data

Encapsulated	No
--------------	----

Capabilities

Dimmable	Yes
Dimming interface	DALI / Touch DIM / Touch DIM Sensor
Dimming range	0.1...100 % ¹⁾
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Type of connection, output side	Screw connection

¹⁾ With AC / 1...100% with DC

Certificates & Standards

Approval marks – approval	E1 approval / VDE / VDE-EMC
Standards	Acc. to EN 55015:2006 + A1:2007 / Acc. to EN 61000-3-2 / Acc. to EN 61547 / Acc. to EN 61347-2-2
Protection class	II
Type of protection	IP20








LOGISTICAL DATA


Temperature range at storage	-40...+85 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Networked standby power for CLS	0.50 W
---------------------------------	--------

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	334136_Technical guide - HALOTRONIC for low-voltage halogen lamps
 User instruction / safety instructions	334563_HALOTRONIC INTELLIGENT – Manual
 Declarations of conformity	710835_EC-DOC Halotronic
 Certificates	VDE EMC Certificate 40024187
 Certificates	HALOTRONIC EMC 134590 080720
 Certificates	VDE ENEC Certificate 40024665
 Certificates	504178_EAC HT family

CAD/BIM files	Document name
 CAD data 3D PDF	317451_HTL 105/230-240 and HTL 225/230-240 9900052

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321420633	Unpacked 1		160.00 g	
4008321420640	Shipping box 10	235 mm x 89 mm x 183 mm	1711.00 g	3.83 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.