

PRODUCT DATASHEET

OTe 35/220...240/700 PC

OPTOTRONIC® Phase-cut OTE | Compact constant current LED drivers



Areas of application

- Optional cable clamp E-style for independent mounting
- Suitable for indoor installations
- Suitable for indoor SELV installations

Product benefits

- Compact housing for mounting in very tight spaces
- Compatible with the most common leading-edge and trailing-edge phase dimmers

Product features

- Dimmable via leading edge/trailing edge
- Type of protection: IP20

TECHNICAL DATA

Electrical data

Nominal wattage	35.00 W
Nominal output power	35 W ¹⁾
Nominal voltage	220...240 V
Nominal output voltage	27...50 V ²⁾
Input voltage AC	195...264 V ³⁾
U-OUT (working voltage)	58 V
Nominal current	0.18 A
Nominal output current	700 mA ⁴⁾
Inrush current	10 A ⁵⁾
Output current tolerance	±5 %
Output ripple current (100 Hz)	< 35 % ⁶⁾
Mains frequency	50/60 Hz
Power factor λ	0.95 ⁷⁾
ECG efficiency	87 % ⁸⁾
Device power loss	7 W ⁹⁾
Max. ECG no. on circuit breaker 10 A (B)	32
Max. ECG no. on circuit breaker 16 A (B)	50
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Power loss in stand-by mode	< 1 W

1) Partial load 19...35 W

2) Maximum < 58 V

3) Permitted voltage range

4) ±5%

5) $t_{\text{width}} = 250 \mu\text{s}$ (measured at 50 % I_{peak})

6) Typical

7) Full load at 230 V/Minimum load at 230 V


8) At full load and 230 V

9) Maximum

Photometrical data

Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.8

Dimensions & Weight



Length	153.00 mm
Mounting hole spacing, length	146,0 mm
Width	54.00 mm
Height	36.00 mm
Cable cross-section, input side	0,75...2,5 mm² 1)
Cable cross-section, output side	0,5...2,5 mm² 1)
Wire preparation length, input side	8,0 mm
Wire preparation length, output side	6,0 mm
Product weight	165.00 g

1) Flexible / Solid leads

Colors & materials

Casing material	Plastic
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	75 °C 1)
Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % 2)

1) Maximum at the Tc-point
2) Maximum 56 days/year at 85 %

Lifespan

ECG lifetime	50000 h 1)
--------------	------------

1) At T_{case} = 65°C at T_c point / 10% failure rate

Additional product data

Encapsulated	No
--------------	----

Capabilities

Dimmable	Yes
Dimming interface	Phase Cut ¹⁾
Dimming range	10...100 %
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
No-load proof	Yes
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2,0 m
Suitable for fixtures with prot. class	I / II
Type of connection, output side	Push terminal

¹⁾ Leading edge / Trailing edge








Certificates & Standards

Approval marks – approval	CE / ENEC 10 / VDE / CB / C-Tick
Standards	Acc. to IEC 61347-1 / Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to CISPR 15 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / Acc. to IEC 61547
Protection class	II
Type of protection	IP20

LOGISTICAL DATA

Temperature range at storage	-40...+85 °C
------------------------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	343883_Dimmer Compatibility List_OTe 35/220-240/700 PC
	User Instruction	544631_OT PC dimmer list
	Declarations of conformity	EU Declaration of Conformity 3668420
	Declarations of conformity	727840_Declaration OTe 35
	Declarations of conformity	EU Declaration of Conformity 3365230
	Certificates	VDE ENEC Certificate 40038447
	Certificates	OTE 35 700 PC CB DE1 63216 040320

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321825520	Unpacked 1		165.00 g	
4008321825537	Shipping box 10	276 mm x 98 mm x 166 mm	1812.00 g	4.49 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.