




## TECHNICAL DATA

### Electrical data

Nominal wattage	0.35 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz

### Dimensions & Weight



Length	118.00 mm
Width	30.00 mm
Height	21.00 mm
Product weight	50.00 g

### Colors & materials

Product color	Light grey
---------------	------------

### Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

### Additional product data

Number of control outputs	1
---------------------------	---

### Capabilities

Dimmable	No
Dimming interface	DALI-2
Number of control outputs	1
Type of installation	Ceiling integration/Luminaire integration



### Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

## EQUIPMENT / ACCESSORIES

- HF LS LI - Light and presence Sensor head with HF technology (radar)
- Separate installation possible with ECO CI KIT

DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	DALI2 COUPLER HF
	Declarations of conformity	DALI SENSOR LS PD LI

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172072199	Folding box 1	128 mm x 37 mm x 27 mm	49.00 g	0.13 dm <sup>3</sup>
4062172072205	Shipping box 25	200 mm x 140 mm x 147 mm	1670.00 g	4.12 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.