

# PRODUCT DATASHEET

## SMART+ Wifi Table Frame MAX Powerbank USB RGB + W

Smart+ Table Frame Maxi Multicolor | Outdoor Smart table frame maxi Luminaire



### Areas of application

- Gardens
- Patios, balconies
- General illumination

### Product benefits

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options
- USB chargeable for mobile use (cable included, fully charged in 6h)
- Integrated Powerbank
- High-quality materials

### Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Type of protection: IP44



## TECHNICAL DATA

### Electrical data


Nominal wattage	5.00 W
Nominal voltage	5 V
Nominal current	1000.000 mA
Protection class	III

### Photometrical data

Luminous flux	270 lm
Total luminous flux of contained light sources	310 lm
Luminous efficacy	54 lm/W
Color temperature	3000 K
Light color (designation)	Warm White / RGB
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdc <sub>m</sub>
Flickering metric (Pst LM)	
Photobiological safety group acc. to EN62778	RG0
Beam angle	270 °

### Dimensions & Weight

Length	140.00 mm
Width	140.00 mm
Height	263.00 mm
Product weight	950.00 g



SMART OD WIFI TABLE FRAME  
MAX PB USB RGBW

### Materials & Colors

Product color	Black
Housing color	Black

Body material	Aluminum Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	USB
Type of protection	IP44
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Application environment	Outdoor
Adjustable	No
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

### BATTERY

Type of Battery	Lithium ion
Battery size [GMS]	18650
Number of included batteries	1
Nominal voltage of battery	3.7 V
Nominal capacity of battery	5200 mAh
Battery charging time	5 h

### Certificates & Standards

Standards	CE / UKCA
Ball shot safe	No





### Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
----------------	--

### EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)
- Complete mounting and connecting accessories included

## DOWNLOAD DATA

Documents and certificates		Document name
	User Instruction	SMART+ WIFI TABLE FRAME
	Declarations of conformity	SMART ODWIFI TABLEFRAME
	Declarations Of Conformity UKCA	SMART ODWIFI TABLEFRAME
	Declarations Of Conformity UKCA	SMART ODWIFI TABLEFRAME MAX

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075763241	Folding box 1	145 mm x 145 mm x 270 mm	1073.00 g	5.68 dm <sup>3</sup>
4058075763258	Shipping box 4	310 mm x 310 mm x 290 mm	4950.00 g	27.87 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- Further information and frequently asked questions (FAQs) at [www.ledvance.com/consumer/smart/faq](http://www.ledvance.com/consumer/smart/faq)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.