




Pushing Performance  
Since 1945

## Han 24B-HTE-PFT-SL-w/o. thread



|               |                                |
|---------------|--------------------------------|
| Part number   | 09 30 024 1102                 |
| Specification | Han 24B-HTE-PFT-SL-w/o. thread |

### Identification

|                          |                            |
|--------------------------|----------------------------|
| Category                 | Hoods/Housings             |
| Series of hoods/housings | Han <sup>®</sup> B         |
| Type of hood/housing     | Panel feed through housing |

### Version

|                            |   |
|----------------------------|---|
| Size                       | 24 B  |
| Version                    | Without cable entry                               |
| Locking type               | Single locking lever                              |
| Han-Easy Lock <sup>®</sup> | Yes   |
| Field of application       | Standard hoods/housings for industrial connectors |

### Technical characteristics

|  |  |
|--|--|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65   |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                  |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |
| Material (seal)         | NBR                  |



**Pushing Performance**  
Since 1945

## Material properties

|  |                                       |
|--|---------------------------------------|
| Material (locking)   | Polycarbonate (PC)<br>Stainless steel |
| Colour (locking)   | RAL 7037 (dust grey)                  |
| Material flammability class acc. to UL 94 (locking levers) | V-0                                   |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
| CE        | Yes    |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 486 g                                    |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |