

## Basic features

Approval/Conformity	CE UKCA cULus WEEE
Scope of delivery	Part label (20x) Port cover M12 (4x) Grounding strap Lock washer Short guide M4x6 screw
Style	Two-row

## Display/Operation

Actuator supply UA, indicator	Green LED
IO-Link communication indicator	Green LED
Module supply indicator	Green LED
Switching function display	LED yellow

## Electrical connection

Connection (COM 1)	M12x1-Male, 4-pin, A-coded
Connection (supply voltage IN)	7/8"-Male, 5-pin
Connection slots	8x M12x1-Female, 5-pin, A-coded
Contact, surface protection	nickel plated 2 µm/gold plated 0.4 µm

## Electrical data

Configurable inputs/outputs	no
Current consumption without load, max.	90 mA
Current sum UA, actuator	9.0 A
Current sum US, sensor	4.0 A
IO-Link function	Device
IO-Link ports, number	1
Operating voltage Ub	18...30.2 VDC
Rated operating voltage Ue DC	24 V
Switching current	16x 2 A

I/O modules

BNI IOL-256-000-Z013

Order Code: BNI0034

**BALLUFF**

### Environmental conditions

Ambient temperature	-5...70 °C
Ambient temperature UL max.	45 °C
EN 60068-2-6, Vibration	5...61 Hz, constant amplitude 1 mm 61...500 Hz, constant acceleration 15 g
IP rating	IP67, when threaded in
Storage temperature	-25...70 °C

### Functional safety

MTTF (40 °C)	67 a
--------------	------

### IO-Link

IO-Link Profil IDs	N/A
--------------------	-----

### Interface

Cycle time min.	3 ms
Digital outputs	16x PNP
IO-Link version	1
Interface	IO-Link 1.0
Process data OUT	2 bytes
Process data cycle min.	3 ms
Transfer rate	COM2 (38.4 kBaud)

### Material

Gasket, material	FKM 75
Housing material	Die-cast zinc, nickel-plated
Housing shield	yes
Surface protection	Cu 15 µm Ni 15 µm

### Mechanical data

Dimension	68 x 32.4 x 181.5 mm
Mounting ground strap	M4 internal thread
Mounting part	2-hole screw mount


### Remarks

See short guide

For more information about MTTF and B10d see MTTF / B10d Certificate


Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings




### Output Ports

- PIN 1: not used
- PIN 2: Output 2
- PIN 3: GND
- PIN 4: Output 1
- PIN 5: Function ground



### Power IN

- PIN 1: GND,reference pot. Segment1
- PIN 2: GND, reference potential, Segment2
- PIN 3: Function ground
- PIN 4: +24V, UA Segment2
- PIN 5: +24V, UA Segment1



### IO-Link

- PIN 1: +24V
- PIN 2: not used
- PIN 3: GND
- PIN 4: C/Q, IO-Link DC-Channel