

Single Pole Distribution Blocks Range



| Part number | Article number | Max IEC Current | Line side : Nbre of connection | Line side Min and Max conductor size | Load side : Nbre of connection | Load side Min and Max conductor size | Depth | Height | Width |
|---------------|--|-----------------|--|---|---|---|----------|----------|----------|
| UD-80A |  569010 | 80 A |  1 Cable | 6 - 16 mm ² #16 - # 4 AWG |  6 Cables | 2.5 - 16 mm ² #16 - # 4 AWG | 46 mm | 69 mm | 30 mm |
| UDJ-125A |  569020 | 125 A |  1 Cable | 10 - 35 mm ² #8 - 1/0 AWG |  7 Cables | 2.5 - 16 mm ² #14 - # 4 AWG | 46 mm | 77 mm | 29 mm |
| UDJ-160A |  569030 | 160 A |  1 Cable | 10 - 70 mm ² #8 - 3/0 AWG |  7 Cables | 2.5 - 16 mm ² #14 - # 4 AWG | 46 mm | 77 mm | 29 mm |
| UD-250A |  569040 | 250 A |  1 Cable | 35 - 120 mm ² #6 AWG - 250 kcmil |  11 Cables | 2.5 - 35 mm ² #14 - # 1 AWG | 50 mm | 96 mm | 49 mm |
| UDF-250A |  569041 | 250 A |  Flat Conductor | Flexibar 3X9X0.8 - 6x15.5x0.8 |  6 Cables | 2.5 - 16 mm ² #14 - # 4 AWG | 46 mm | 79 mm | 29 mm |
| UD-400A |  569050 | 400 A |  1 Cable | 95 - 185 mm ² 3/0 AWG - 400 kcmil |  11 Cables | 2.5 - 35 mm ² #14 - # 1 AWG | 50 mm | 96 mm | 49 mm |
| UD-400112AL |  569252 | 400 A |  1 Cable | 95 - 185 mm ² 3/0 AWG - 400 kcmil |  12 Cables | 2.5 - 10 mm ² #14 - # 6 AWG | 50 mm | 96 mm | 55.73 mm |
| UD-400112CU |  569052 | 400 A |  1 Cable | 95 - 185 mm ² 3/0 AWG - 400 kcmil |  12 Cables | 2.5 - 10 mm ² #14 - # 6 AWG | 50 mm | 96 mm | 55.73 mm |
| UD-400212AL |  569251 | 400 A |  2 Cables | 35 - 95 mm ² #8 - 3/0 AWG |  12 Cables | 2.5 - 10 mm ² #14 - # 6 AWG | 50 mm | 96 mm | 55.73 mm |
| UD-400212CU |  569051 | 400 A |  2 Cables | 35 - 95 mm ² #8 - 3/0 AWG |  12 Cables | 2.5 - 10 mm ² #14 - # 6 AWG | 50 mm | 96 mm | 55.73 mm |
| UDF-500A |  569060 | 500 A |  Flat Conductor | Flexibar 4x15.5x0.8 - 8x24x1 |  11 Cables | 2.5 - 35 mm ² #14 - # 1 AWG | 50 mm | 96 mm | 49 mm |
| UD6C500AL |  569201 | 500 A |  1 Cable | 95 - 240 mm ² 3/0AWG- 500 kcmil |  6 Cables | 10 - 50 mm ² #8 - 1/0 AWG | 148.1 mm | 90.2 mm | 43.7 mm |
| UDF6C500AL |  569202 | 500 A |  Flat Conductor | Flexibar 2x20x1 - 10x24x1 IBS/IBSB 50 - 100 mm ² |  6 Cables | 10 - 50 mm ² #8 - 1/0 AWG | 148.1 mm | 90.2 mm | 43.7 mm |
| UDF9C500AL |  569204 | 500 A |  Flat Conductor | Flexibar 2x20x1 - 10x24x1 IBS/IBSB 50 - 100 mm ² |  9 Cables | 4 - 25 mm ² #12 - # 4 AWG | 127 mm | 78 mm | 43.7 mm |
| UDF12C500AL |  569206 | 500 A |  Flat Conductor | Flexibar 2x20x1 - 10x24x1 IBS/IBSB 50 - 100 mm ² |  12 Cables | 4 - 25 mm ² #12 - # 4 AWG | 127 mm | 78 mm | 43.7 mm |
| UD9C630AL |  569203 | 630 A |  1 Cable | 120 - 300 mm ² 4/0 AWG- 600 kcmil |  9 Cables | 4 - 25 mm ² #12 - # 4 AWG | 127 mm | 78 mm | 43.7 mm |
| UD2C12C630AL |  569205 | 630 A |  2 Cables | 95 - 185 mm ² 3/0 AWG - 400 kcmil |  12 Cables | 4 - 25 mm ² #12 - # 4 AWG | 127 mm | 78 mm | 43.7 mm |
| UDF12C800AL |  569208 | 800 A |  Flat Conductor | Flexibar 2x20x1 - 10x32x1 IBS/IBSB 50 - 240 mm ² |  12 Cables | 4 - 25 mm ² #12 - # 4 AWG | 147.3 mm | 79.8 mm | 55.2 mm |
| UD2C12C1000AL |  569207 | 1000 A |  2 Cables | 35 - 240 mm ² 2 AWG - 500 kcmil |  12 Cables | 4 - 25 mm ² #12 - # 4 AWG | 147.3 mm | 79.8 mm | 55.2 mm |
| UDF9C1000AL |  569210 | 1000 A |  Flat Conductor | Flexibar 6x24x1 - 10x50x1 IBS/IBSB 120 - 240 mm ² |  9 Cables | 10 - 95 mm ² #8 - 3/0 AWG | 195.6 mm | 105.9 mm | 70.5 |
| UD2C9C1250AL |  569209 | 1250 A |  2 Cables | 185 - 400 mm ² 400 kcmil - 750 kcmil |  9 Cables | 10 - 95 mm ² #8 - 3/0 AWG | 195.6 mm | 105.9 mm | 70.5 |