

## BUSBAR VOOR AARDING EN N-GELEIDER, BLANK KOPER, 133 AANSLUITINGEN, 30 MM<sup>2</sup>

### CATALOG NUMBER

## EBC133-10X3X2000



EBC-133 Earthing and Neutral Busbars are used to connect multiple earthing conductors within a panel and can be used in a variety of different applications including switchgear and control equipment, electrical equipment, wind and solar power generation, data centers and in power distribution application.

EBC-133 Earthing and Neutral Busbar can be fixed using IRS Angle Support Bracket, DMH Metallic Spacer or DH Distance Holder and Spacer.

### CERTIFICATIONS



### FEATURES

Easy for the installer to add connections

Clamps are fully assembled

Clamps follow the screw vertically, making it quick and easy to mount the conductor

Op de gewenste lengte te snijden

Main terminal clamp available for thicker conductors

Can be connected to IBSB25 Insulated Braided Conductor, MJB Grounding and Bonding Braid, and nVent ERIFLEX Flexibar up to 9 mm (0.354")

Snelle en eenvoudige installatie

RoHS compliant

### PRODUCTKENMERKEN

Article Number: 568612

Material: Copper;Steel

Finish: Elektrolytisch gegalvaniseerd

Number of Connections: 133

Conductor Size, IEC: (133) 0,5 - 16 mm<sup>2</sup> Solid;(133) 0,5 - 10 mm<sup>2</sup> Stranded

Conductor Width: Max. 9 mm

Max Current Rating: 108A

Cross Section: 30 mm<sup>2</sup>

Depth (D): 10 mm

Width (W): 2000 mm

Thickness (T): 3 mm

A: 15 mm


B: 4,8 mm

Thread Size (TS): M5

Torque (TQ): 2,5 N·m

Unit Weight: 1 kg

## DIAGRAMS



## WAARSCHUWING

Producten van nVent moeten worden geïnstalleerd en gebruikt op de manier zoals is aangegeven in de nVent productinformatiebladen en trainingsmaterialen. U kunt de productinformatiebladen downloaden van [www.nvent.com](http://www.nvent.com) of opvragen bij uw nVent-klantenservice. Door onjuist installeren, verkeerd gebruik, verkeerde toepassing of enige andere handeling in strijd met de instructies en waarschuwingen van nVent kan het product mogelijk niet correct werken, ernstig of fataal letsel en materiële schade veroorzaken en/of uw garantie ongeldig maken.

### Noord-Amerika

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

### Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

### Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

### APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:  
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**