


START DOWNLIGHT 150 IP44
START Downlight 150 IP44 1250lm 840
0030325



Product features

- Ceiling recessed LED downlight IP44 (from the front), perfect where limited ceiling void is available with only 45mm product depth and 150mm cutout. Ideal replacement for 1x26W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Loop in loop out connector allows for quick installation. Die-cast aluminium body, 12W, 4000K, Driver Current: 290mA, CRI80, 74° beam angle, Non-dimmable LED driver, IP44 from the front, IK07, (HxW) 45x165mm, Class 2, 220-240V. Meets TP(a) requirements.




PRODUCT OVERVIEW

Product name	START Downlight 150 IP44 1250lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Logistics & Industry, Office
ETIM Class	EC001744
E-number FI	4278146
Warranty	5 years
Useful luminous flux (Fuse)	1175
Fixture luminous flux (lm)	1250
Luminous flux (lm)	1250
Luminaire efficacy (lm/W)	104
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	74
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	12
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9010 - Pure white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303253

START DOWNLIGHT 150 IP44
START Downlight 150 IP44 1250lm 840
0030325

PHOTOMETRY



TECHNICAL DRAWINGS

