

START Waterproof Slim 1500 IP65 3800lm 840
0046371



Features

- START Waterproof Slim is a LED integrated polycarbonate housing luminaire with easy to access electrical terminal through bayonet lock end caps and tool-free electrical connection due to push-in terminal. Flexible installation as mounting brackets can be positioned freely on the luminaire. 28W; 3800lm; High efficiency with 136lm/W and 100,000 hours lifespan L70B50. SDCM < 5; IP65; IK08; Class I; 1488mm x 70mm x 69mm.


Product Overview

Product name	START Waterproof Slim 1500 IP65 3800lm 840
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4357077
Fixture luminous flux (lm)	3800
Luminaire efficacy (lm/W)	136
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	5
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	28
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	Grey

**START Waterproof Slim 1500 IP65 3800lm 840
0046371**

IP rating	IP65
IK rating	IK08
Product EAN number	5410288463711
Warranty	5 years
Dimming method	N/A

Photometry



Technical drawings

