

ToLEDo MicroLynx V2 650LM 840 SL

Item No: 0029697

SYLVANIA




Sleek and compact design Low energy consumption Instant light at the flick of switch No glare thanks to frosted diffuser 15,000 hours rated lamp life Good colour rendering - CRI80 Non-dimmable 3 years warranty The perfect lamp for cabinet lighting in kitchens, bedrooms and for displays and showcases

Technical Assets

Dimensions (mm)

Photometrics



ToLEDo MicroLynx V2 650LM 840 SL

Item No: 0029697

SYLVANIA

General data

Product name	ToLEDo MicroLynx V2 650LM 840 SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	GX53
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741149
Warranty	3 years

Optical data

Useful luminous flux (Φ_{use})	650
Luminous flux (lm)	650
Luminous flux (Rated) (lm)	650
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	6.5
Wattage (W)	6.5
Equivalent watt (W)	50
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	2.8
Inrush Duration (μ s)	380
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	57
Max. products per 16A B Breaker	29

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	75
Nominal Product Diameter (mm)	25
Weight (kg)	0.048

ToLEDo MicroLynx V2 650LM 840 SL

Item No: 0029697



Packaging

Product EAN number	5410288296975
Packaging single length / height (cm)	7.6
Packaging single width (cm)	2.7
Packaging single depth (cm)	7.6
DUN14 (inner)	15410288296972
Units per outer package	6
Packaging outer length / height (cm)	16.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	8.4

Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures