

Sylproof Tubular LED - Electronic

Sylproof Tubular LED 2X600 EB NW
0047583



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED



PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 2X600 EB NW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Useful luminous flux (Fuse)	2269
Fixture luminous flux (lm)	2269
Luminous flux (lm)	2269
Luminaire efficacy (lm/W)	108.04
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	21
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Dimming method	N/A
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288475837


PHOTOMETRY

Sylproof Tubular LED - Electronic Sylproof Tubular LED 2X600 EB NW 0047583

Distance [m]	Cone diameter [m]	E ₀ [lx]	E _{10%} [lx]	E _{5%} [lx]
0.5	1.13 2.16	2811	48.9° 34°	88.2° 57°
1.0	2.26 4.33	698	48.9° 34°	88.2° 57°
1.5	3.39 6.48	292	48.9° 34°	88.2° 57°
2.0	4.52 8.66	161	48.9° 34°	88.2° 57°
2.5	5.65 10.82	105	48.9° 34°	88.2° 57°
3.0	6.78 12.99	73	48.9° 34°	88.2° 57°

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 180°)
— C90 - C270 (Half beam angle: 90°)



TECHNICAL DRAWINGS

