




## mof

- PE100 SDR11 (ISO S5)
- 10 bar gas / 16 bar water
- 4 mm stekker aansluiting
- begrenste lasindicator
- verwijderbare middenaanslag tot d160



d [mm]	Code	GP	gewicht [kg]	d1 [mm]	L [mm]
75	<b>753 911 612</b>	12	0,282	96	110
90	<b>753 911 613</b>	10	0,406	113	125
110	<b>753 911 614</b>	5	0,692	138	145
125	<b>753 911 615</b>	5	0,718	154	156
140	<b>753 911 616</b>	5	0,945	172	166
160	<b>753 911 617</b>	6	1,362	196	180
180	<b>753 911 618</b>	5	1,747	219	192
200	<b>753 911 619</b>	4	1,866	244	208
225	<b>753 911 620</b>	3	3,329	273	225
250	<b>753 911 621</b>	2	4,678	304	248
280	<b>753 911 622</b>	2	7,500	340	252
315	<b>753 911 623</b>	1	8,142	382	267

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland  
Phone +41 -(0)52-631 1111  
e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)  
Internet: <http://www.gfps.com>