



96 kniekoppeling mit konische dichting

- Torque and notes for installation please find in "Technical Product Notes".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- * binnenzeskant

EN 10242	diameter (inch)	dimensie (Gew. 374 »G«) (inch)	Black Code	Galvanised Code	SP	GP
•	¼	⅝	770 096 102	770 096 202	0	120
•	⅜	¾	770 096 103	770 096 203	0	40
•	½	1	770 096 104	770 096 204	10	60
•	¾	1 ¼	770 096 105	770 096 205	10	40
•	1	1 ½	770 096 106	770 096 206	0	25
•	1 ¼	2	770 096 107	770 096 207	0	12
•	1 ½	2 ¼	770 096 108	770 096 208	0	20
•	2	2 ¾	770 096 109	770 096 209	0	5
-	2 ½	3 ½	770 096 110	770 096 210	0	4
-	3	4	770 096 111	770 096 211	0	4

EN 10242	diameter (inch)	dimensie (Gew. 374 »G«) (inch)	a (mm)	c (mm)	z1 (mm)	z2 (mm)	s1 (mm)	s2 (mm)
•	¼	⅝	48	21	11	38	*10	28
•	⅜	¾	52	25	15	42	*12	32
•	½	1	58	28	15	45	25	41
•	¾	1 ¼	62	33	18	47	32	48
•	1	1 ½	72	38	21	55	38	55
•	1 ¼	2	82	45	26	63	48	67
•	1 ½	2 ¼	90	50	31	71	54	74
•	2	2 ¾	100	58	34	76	66	90
-	2 ½	3 ½	130	72	45	103	85	111
-	3	4	134	79	49	104	96	131

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>