



331 koppeling flach dichtendohne Dichtringe geliefert. b en z2 includieren die Dichtungsstärke lt. tabel

- Supplied without sealing gaskets; b and z2 include the seal thickness as per table "Sealing Gasket Dimension".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.

EN 10242	diameter (inch)	dimensie (Gew. 374 »G«) (inch)	Black Code	Galvanised Code	SP	GP
•	¼	⅝	770 331 102	770 331 202	0	150
•	⅜	¾	770 331 103	770 331 203	10	40
•	½	1	770 331 104	770 331 204	10	70
•	¾	1 ¼	770 331 105	770 331 205	10	40
•	1	1 ½	770 331 106	770 331 206	0	30
•	1 ¼	2	770 331 107	770 331 207	0	15
•	1 ½	2 ¼	770 331 108	770 331 208	0	10
•	2	2 ¾	770 331 109	770 331 209	0	8
-	2 ½	3 ½	770 331 110	770 331 210	0	4
-	3	4	770 331 111	770 331 211	0	6

EN 10242	diameter (inch)	dimensie (Gew. 374 »G«) (inch)	b (mm)	z2 (mm)	s1 (mm)	s2 (mm)	s3 (mm)
•	¼	⅝	55	45	19	28	15
•	⅜	¾	58	48	22	32	19
•	½	1	66	53	26	41	23
•	¾	1 ¼	72	57	31	48	30
•	1	1 ½	80	63	38	55	36
•	1 ¼	2	90	71	48	67	48
•	1 ½	2 ¼	95	76	54	74	54
•	2	2 ¾	107	83	66	90	66
-	2 ½	3 ½	118	91	85	111	85
-	3	4	131	101	96	130	95

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>