



330 koppeling flach dichtendohne Dichtringe geliefert.a en z1 includieren die Dichtungsstärke lt. tabel

- Supplied without sealing gaskets; a and z1 include the seal thickness as per table "Sealing Gasket Dimension".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- * binnenzeskant

EN 10242	diameter (inch)	dimensie (Gew. 374 »G«) (inch)	Black Code	Galvanised Code	SP	GP
•	1/4	5/8	770 330 102	770 330 202	0	60
•	3/8	3/4	770 330 103	770 330 203	10	40
•	1/2	1	770 330 104	770 330 204	10	70
•	3/4	1 1/4	770 330 105	770 330 205	10	50
•	1	1 1/2	770 330 106	770 330 206	0	30
•	1 1/4	2	770 330 107	770 330 207	0	20
•	1 1/2	2 1/4	770 330 108	770 330 208	0	15
•	2	2 3/4	770 330 109	770 330 209	0	10
•	2 1/2	3 1/2	770 330 110	770 330 210	0	5
•	3	4	770 330 111	770 330 211	0	8
-	4	5	770 330 112	770 330 212	0	4

EN 10242	diameter (inch)	dimensie (Gew. 374 »G«) (inch)	a (mm)	z1 (mm)	s1 (mm)	s2 (mm)	s3 (mm)
•	1/4	5/8	42	22	19	28	*10
•	3/8	3/4	47	27	22	32	*12
•	1/2	1	48	22	26	41	26
•	3/4	1 1/4	52	22	31	48	31
•	1	1 1/2	59	25	38	55	38
•	1 1/4	2	65	27	48	67	48
•	1 1/2	2 1/4	70	32	54	74	54
•	2	2 3/4	80	32	66	90	66
•	2 1/2	3 1/2	85	31	85	111	85
•	3	4	96	36	96	130	96
-	4	5	111	39	120	151	122

De technische gegevens zijn niet bindend en houden geen garanties in van eigenschappen. Wijzigingen voorbehouden. Onze algemene verkoopvoorwaarden zijn van toepassing.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>